

# AirChek XR5000 Sample Pump

**Supercharged Li-Ion Battery Power!**

**Flows: 5 to 5000 ml/min**



Top view



Two battery options

Ⓞ **Extended flow range: 5 to 5000 ml/min†**

- Suitable for low flow gas/vapor or high flow particulate sampling
- All-in-One adjustable tube holder for single-tube sampling
- Optional multiple low flow holders used with CPC allow up to four tube samples to be taken simultaneously, each at different flow rates if desired

Ⓞ **Enhanced battery power for extended run times\***

XR5000 Model	2 L/min	5 L/min
High-power Li-Ion	40 hours	22 hours
Standard Li-Ion	20 hours	11 hours

\* Results of run time tests using 37-mm, 0.8-µm MCE filters with new pumps and batteries. Pump and battery performance may vary.

Ⓞ **Extended back pressure capabilities**

- Up to 50 inches water at 2 L/min

Ⓞ **Highly accurate isothermal flow control system**

Ⓞ **Extremely simple to use**

- Large three-button keypad
- Set-and-go timer for timed and delayed runs to 9999 minutes
- Continuous run with the touch of a button
- Large LCD displays elapsed time and accumulated run time
- Bright blue pump status LED

Ⓞ **Automatic features for sample integrity**

- Flow correction for changes in temperature
- Lockable keypad
- Flow fault indicator
- Auto-restart from flow fault
- Accumulated run time display
- Battery status indicator

Ⓞ **Two interchangeable battery options**

- High-power Li-Ion for extended runs
- Standard Li-Ion for lighter weight

Ⓞ **Standard model weighs only 16 ounces (454 grams)**

Ⓞ **UL Listed for intrinsic safety**

Ⓞ **The first RoHS compliant sample pump!**

- Components meet Euro directive for reduction of hazardous substances (including lead) to support green initiatives

† 5 to 500 ml/min with Low Flow Adapter Kit





## Quick View

### AirChek XR5000 Sample Pump

Performance Profile	
<b>Flow Control Accuracy</b>	± 5% of set-point after calibration to desired flow
<b>Timing Accuracy</b>	1 min/mo at 25 C
<b>Typical Run Time</b>	<b>Standard Li-Ion battery:</b> 20 hrs <b>High-power Li-Ion battery:</b> 40 hrs <b>Charger:</b> Extended runs when attached to charger
<b>Charge Time</b> <i>(varies with capacity and level of charge)</i>	<b>Standard 2-cell Li-Ion:</b> Approximately 4 hrs <i>(with approved charger)</i> <b>High-power 4-cell Li-Ion:</b> Approximately 8 hrs <i>(with approved charger)</i>
<b>Temperature Range</b>	<b>Operating:</b> 32 to 104 F (0 to 40 C) <b>Charging:</b> 32 to 113 F (0 to 45 C) <b>Storage:</b> -4 to 95 F (-20 to 35 C)
<b>Timer Display Range</b>	1 to 9999 min (6.8 days); display rolls over to 0 upon reaching 9999 min
<b>Auto-off</b>	After 5 min of inactivity
<b>Flow Fault</b>	After 15 sec, pump stops, holds run time display, and displays fault icon. After 15 sec in fault, auto-restart is attempted every 15 sec up to 5 times
<b>Low Battery Fault</b>	15 sec to sleep

### Ordering Information

AirChek XR5000 Pumps require 1/4-inch ID tubing.

#### AirChek XR5000 with High-power Li-Ion<sup>‡</sup>

Pump and Kits	Cat. No.	
<b>Pump with battery</b> and screwdriver set, <i>requires charger, see kits or chargers below</i>		210-5001
<b>Starter Kit</b> includes pump, charger, Tygon tubing (3 feet, 1/4-inch ID), and collar clip with cable tie	100-240 V	210-5001-S
<b>Single Pump Kit</b> includes pump, charger, and cassette holder, in a soft-side nylon carry case	100-240 V	210-5001K
<b>5-pack High Flow Pump Kit</b> includes 5 pumps and cassette holders and Take Charge 5 Multi-charger, in a Pelican case	100-240 V	210-5001K5
<b>5-pack High/Low Flow Pump Kit</b> includes 5 pumps, cassette holders, All-in-One adjustable tube holders, and Type A protective tube covers and Take Charge 5 Multi-charger, in a Pelican case	100-240 V	210-5001K5D
<b>Replacement 4-cell Li-Ion Battery Pack</b>		P85004

<sup>‡</sup> AirChek XR5000 pumps contain Li-Ion batteries and are subject to special shipping regulations.

#### AirChek XR5000 with Standard Li-Ion<sup>‡</sup>

Pump and Kits	Cat. No.	
<b>Pump with battery</b> and screwdriver set, <i>requires charger, see kits or chargers below</i>		210-5002
<b>Starter Kit</b> includes pump, charger, Tygon tubing (3 feet, 1/4-inch ID), and collar clip with cable tie	100-240 V	210-5002-S
<b>Single Pump Kit</b> includes pump, charger, and cassette holder, in a soft-side nylon carry case	100-240 V	210-5002K
<b>5-pack High Flow Pump Kit</b> includes 5 pumps and cassette holders and Take Charge 5 Multi-charger, in a Pelican case	100-240 V	210-5002K5
<b>5-pack High/Low Flow Pump Kit</b> includes 5 pumps, cassette holders, All-in-One adjustable tube holders, and Type A protective tube covers and Take Charge 5 Multi-charger, in a Pelican case	100-240 V	210-5002K5D
<b>Replacement 2-cell Li-Ion Battery Pack</b>		P85002

<sup>‡</sup> AirChek XR5000 pumps contain Li-Ion batteries and are subject to special shipping regulations.

Accessories	Cat. No.	
<b>Chargers</b>		
<b>Single</b>	100-240 V	223-241
<b>Take Charge 5 Multi-charger</b>	100-240 V	223-441
<b>Low Flow Kit (5 to 500 ml/min)</b> includes All-in-One adjustable tube holder and Type A protective tube cover, <i>suitable for both XR5000 models</i>		210-500
<b>Protective Pouches</b> , nylon, with belt, adjustable waist, and shoulder strap		
<b>Black</b> , for high-power model		224-88
<b>Red, high-profile</b> , for high-power model		224-96A
<b>Black, noise-reducing</b> , for high-power model		224-96C
<b>Black, noise-reducing</b> , for standard model		224-913

### SKC Limited Warranty and Return Policy

SKC products are subject to the SKC Limited Warranty and Return Policy, which provides SKC's sole liability and the buyer's exclusive remedy. To view the complete SKC Limited Warranty and Return Policy, go to <http://www.skcinc.com/warranty.asp>.

<b>Flow Rate (ml/min)</b>	5 to 5000
<b>Weight in Ounces (grams)</b>	16 (454), 2 cell Li-Ion Model
<b>Compensation Range (inches water)</b>	Up to 10 at 5 L Up to 50 at 2 L
<b>Built-in Timer/Clock</b>	Timer
<b>Constant Flow</b>	Yes
<b>Programmable</b>	Yes
<b>PC-compatible</b>	N/A
<b>Multi-tube Sampling</b>	Yes
<b>Flow Fault Feature</b>	Yes
<b>RF/EMI Shielded</b>	Yes
<b>Intrinsically Safe — cUL US Listed</b>	Yes
<b>MSHA-approved Models Available</b>	N/A
<b>ATEX Models Available</b>	N/A
<b>CE Marked</b>	Yes
<b>RoHS Compliant</b>	Yes
<b>Corrects for Changes in Atmospheric Pressure</b>	N/A
<b>Corrects for Changes in Temperature</b>	Yes
<b>Battery Type</b>	High-power Li-Ion (7.4 V, 4.4 Ah, 32.6 Wh) Standard Li-Ion (7.4 V, 2.2 Ah, 16.3 Wh)
<b>Battery Check</b>	Yes
<b>Tubing</b>	Requires 1/4-inch ID tubing

Recommended Accessories
Chargers
Low Flow Kit
Cat. No. 210-500
Adjustable Low Flow Tube Holders
Filter Holders
Tubing
Cases/Pouches